



FITTING INSTRUCTIONS FOR ECC0348R
RHS CLUTCH CASE COVER
HONDA MSX 125 GROM 2021-



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

**IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS
OR HAVE FITTED BY A QUALIFIED TECHNICIAN.**

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF
MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,
THESE RUBBER WASHERS CAN BE THROWN AWAY.

DIGITAL COPIES OF THESE INSTRUCTIONS ARE AVAILABLE FROM:

WWW.RG-RACING.COM



<u>TOOLS REQUIRED</u>	<u>GENERAL TORQUE SETTINGS</u>
<ul style="list-style-type: none"> • Set of allen keys to include 3mm, 4mm & 5mm • 8mm & 10mm spanner or socket 	<p>M4 BOLT = 8Nm M5 BOLT = 12Nm M6 BOLT = 15Nm M8 BOLT = 20Nm M10 BOLT = 40Nm M12 BOLT = 40Nm</p>

LEGEND

ITEM NO.	DESCRIPTION	QTY
ITEM 1	ECC0348R ENGINE CASE COVER INCLUDING FITTED SPACERS	1
ITEM 2	M6 x 1.00 x 45mm CAP HEAD BOLT	4

FITTING DIAGRAM 1





FITTING DIAGRAM 2



FITTING INSTRUCTIONS

Please make sure the engine is cold before fitting the R&G Engine Case Cover.

- To fit the R&G engine case cover remove the oil filler cap and 4 x M6 engine case bolts circled in the **Fitting Diagram 1** on Page 2, using an 8mm socket.
- Hold the Engine Case Cover loosely over the case to help identify the correct bolts to remove if necessary.

DO NOT REMOVE ALL OF THE ENGINE CASE BOLTS.

- Ensure the pre-fitted threaded spacers in the casing are hand tight against the inside of the **ECC0348R** Engine Case Cover (**Item 1**).
- Offer up the R&G cover to the engine and carefully fit it over the casing. Ensure that the three bolt holes on the cover are lined up with the holes in the engine casing, and then push it on until it seats up against the engine case.
- Re-fit the oil filler cap.
- Fit the 4x supplied M6 cap head Bolts (**Item 2**) according to **Fitting Diagram 2** (Page 3) through the Engine Case Cover and into the engine casing.

Note:

To avoid cross-threading, apply lateral pressure to the bolt while turning counter-clockwise until a clicking noise is heard/felt, then thread in the bolt.



- Finally use a torque wrench set at 10 N/m (7 Lb/ft) to fully tighten each bolt.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.

Note: For the cleaning of this product, you should only use a soft polishing cloth and a mild general cleaning agent.

AVOID HARMFUL CHEMICALS. IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.

- R&G will accept no liability if the above procedure and torque settings are not followed.
- Check all components are secure and all bolts are tight before running the engine or riding.

ISSUE 1 - 17/03/2022 (TB)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P - at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com