



FITTING INSTRUCTIONS FOR EH0130BKA EXHAUST HANGER



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

PLEASE READ ALL INSTRUCTIONS BEFORE PRECEEDING.

**IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS
OR HAVE FITTED BY A QUALIFIED TECHNICIAN.**

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF
MOUNTING TO THE BIKE.

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY).

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,
THESE RUBBER WASHERS CAN BE THROWN AWAY.




<u>TOOLS REQUIRED</u>	<u>MAXIMUM TORQUE SETTINGS</u>
<ul style="list-style-type: none"> SET OF METRIC ALLEN KEYS <ul style="list-style-type: none"> SOCKET SET TORQUE WRENCH 	<ol style="list-style-type: none"> M4 BOLT = 8Nm M5 BOLT = 12Nm M6 BOLT = 15Nm M8 BOLT = 20Nm M10 BOLT = 40Nm M12 BOLT = 40Nm

LEGEND

ITEM No	DESCRIPTION	QTY
ITEM 1	EXHAUST HANGER (HB0130)	1
ITEM 2	M8 x 1.25 x 15mm BUTTON HEAD BOLT	2
ITEM 3	M8 x 1.25 x 20mm BUTTON HEAD BOLT	2
ITEM 4	M8 x 1.25 x 25mm BUTTON HEAD BOLT	1
ITEM 5	M8 WASHERS	4
ITEM 6	M8 NYLOC NUT	1
ITEM 7	BRANDED WASHER	2

ASSEMBLY DIAGRAM





FITTING INSTRUCTIONS

REMOVE BEFORE FITTING

- Exhaust end can mounting bolt
- Right and left hand side passenger foot peg brackets

RHS EXHAUST BRACKET

1. Once all components are removed, place the new exhaust bracket up to the mounting holes and thread the two 20mm M8 bolts (**ITEM 3**) with a washer (**ITEM 5**) on each bolt, in and tighten. AS SHOWN IN THE ASSEMBLY DIAGRAM.
2. Make sure the OEM exhaust mounting hole is on the inside of the new exhaust bracket.
3. Place the 25mm bolt (**ITEM 4**) with a washer (**ITEM 5**) through the outside of the bracket and through the exhaust hole. The exhaust may need to be wiggled to align the holes.
4. Finally place the last washer (**ITEM 5**) and Nyloc nut (**ITEM 6**) onto the bolt on the back side and tighten.

LHS BLANKING PLATES

1. Place the two 15mm bolts (**ITEM 2**) through the two branded washers (**ITEM 7**).
2. Then insert into the two open holes where the LHS rear footpeg bracket was located.
3. Ensure to tighten all bolts using the General Torque Settings on Page 2.

Please note that it is your responsibility to ensure that no part of the exhaust hanger or exhaust assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.

Issue 1 - 14/03/2025 (JH)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.